

Bujes, roscas y niples

Roscas con tuerca, bujes de reducción y más

Bujes de reducción
Niples de reducción
Roscas con tuerca
Bujes de reducción

Bujes de reducción

Tabla de bujes de reducción

Tamaño		A	B	Ent/caras
pulg.	mm	mm	mm	mm
1/4 x 1/8	6.40	42.00	6.00	16.00
3/8 x 1/4	9.50	47.00	9.00	17.50
1/2 x 3/8	12.70	52.00	11.00	22.00
3/4 x 1/2	19.00	57.00	14.00	27.00
1 x 3/4	25.40	65.00	19.00	36.50
1 1/4 x 1	31.80	72.00	32.50	46.00
1 1/2 x 1 1/4	38.00	74.00	38.00	51.00
2 x 1 1/2	51.00	78.00	49.00	63.50
2 1/2 x 2	63.50	104.00	59.00	76.00
3 x 2 1/2	76.00	108.00	73.50	94.00
4 x 3	102.00	126.00	97.00	117.50

Niples de reducción

Niples de reducción

Tabla de niples de reducción

Ø A x B	Medida		2000-3000				6000				Peso aprox.	
	C		H		E		H		E		3000	6000
pulg.	mm	pulg.	mm	pulg.	mm	pulg.	mm	pulg.	mm	pulg.	mm	mm
3/8 x 1/4	55.00	2.16	11.00	7/16	7.50	19/64	0.05	0.07				
1/2 x 3/8	60.00	2.36	4.00	36/64	11.00	7/16	6.50	17/64	5.00	13/64	0.08	0.10
1/2 x 1/4	60.00	2.36	14.00	35/64	7.50	19/64	0.07	0.10				

Ø A x B	Medida		2000-3000				6000				Peso aprox.	
	C		H		E		H		E		3000	6000
pulg.	mm	pulg.	mm	pulg.	mm	pulg.	mm	pulg.	mm	pulg.	mm	mm
3/4 x 1/2	70.00	2.75	19.00	3/4	14.00	35/64	11.00	7.16	6.50	17/64	0.15	0.22
1 x 3/4	80.00	3.16	24.50	31/32	19.00	3/4	15.00	19.32	11.00	7/16	0.23	0.39
1 x 1/2	80.00	3.16	24.50	31/32	14.00	36/34	15.00	19.32	6.50	17/64	0.21	0.36
1 1/4 x 1	90.00	3.55	32.50	1 9/32	24.50	31/32	23	29.32	15.00	19/32	0.39	0.63
1 1/2 x 1	100.00	3.94	38.00	1 1/2	24.50	31/32	28.00	1 7/64	15.00	19/32	0.53	0.83
1 1/2 x 3/4	100.00	3.94	38.00	1 1/2	19.00	3/4	28.00	1 7/64	11.00	7/16	0.54	0.81
1 1/2 x 1/2	100.00	3.94	38.00	1 1/2	14.00	35/64	28.00	1 7/64	6.50	17/64	0.48	0.72
2 x 1 1/2	110.00	4.33	49.00	1 59/64	38.00	1 1/2	38.50	1 33/64	28.00	1 7/64	0.82	1.31
2 x 1	110.00	4.33	49.00	1 59/64	24.50	35/64	38.50	1 33/64	15.00	19/32	0.78	1.18
2 1/2 x 2	125.00	4.92	59.00	2 21/64	49.00	1 59/64	45.00	1 49/64	38.50	1 33/64	1.23	2.10
3 x 2	145.00	5.70	73.50	2 57/64	49.00	1 59/64	58.50	2 19/64	38.50	1 33/64	2.08	3.40
4 x 3	200.00	7.88	97.00	3 13/16	73.50	2 57/64	80.00	3 5/32	58.50	2 19/64	4.52	7.65
4 x 2	200.00	4.88	97.00	3 13/16	49.00	1 59/64	80.00	3 5/32	38.50	2 19/64	4.35	7.25

Roscas con tuerca

Roscas con tuerca

Tabla de roscas con tuerca

Tamaño		A	B	Ent/caras
pulg.	mm	mm	mm	mm
1/8	3.20	30.00	5.00	12.50
1/4	6.40	42.00	7.00	16.00

Tamaño		A	B	Ent/caras
pulg.	mm	mm	mm	mm
3/8	9.50	47.00	9.00	17.50
1/2	12.70	52.00	11.00	22.00
3/4	19.00	57.00	14.00	27.00
1	25.40	65.00	19.00	36.50
1 1/4	31.80	72.00	32.50	46.00
1 1/2	38.00	74.00	38.00	51.00
2	51.00	78.00	49.00	63.50
2 1/2	63.50	104.00	59.00	76.00
3	76.00	108.00	73.50	94.00
4	102.00	126.00	97.00	117.50

Trabajamos con las normas
ANSI B16.11 • ANSI B2.1 (NPT - WHITWORTH GAS BSPT) - API SB
Relacionados con Bujes, roscas y niples
Caños Epoxi
Tubos sin costura